



**Part Number :** [788641001](#)  
**Product Description :** 1.60mm Pitch Compression Connector, 1.20mm Working Height, Dual Row, 6 Circuits  
**Series Number :** 78864  
**Status :** Active  
**Product Category :** PCB Headers and Receptacles



## Documents & Resources

### Drawings

[788641001\\_sd.pdf](#)  
[PK-78864-001-001.pdf](#)

### 3D Models and Design Files


[788641001\\_stp.zip](#)

### Specifications

[PS-78864-001-001.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

### Industry Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

**Part Details**

**General**

Status	Active
Category	PCB Headers and Receptacles
Series	78864
Description	1.60mm Pitch Compression Connector, 1.20mm Working Height, Dual Row, 6 Circuits
Application	Board-to-Board, Signal
Component Type	PCB Header
Product Name	Battery Connector, Compression Connector
UPC	887191496115

**Electrical**

Current - Maximum per Contact	1.0A
Voltage - Maximum	10V

**Physical**

Breakaway	No
Circuits (Loaded)	6
Circuits (maximum)	6
Color - Resin	Black
Durability (mating cycles max)	30
Glow-Wire Capable	No
Lock to Mating Part	None
Material - Metal	Copper Alloy

Material - Plating Mating	Gold
Material - Plating Termination	Matte Tin
Material - Resin	Liquid Crystal Polymer
Net Weight	0.038/g
Number of Rows	2
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface	1.60mm
Plating min - Mating	0.102μm
Temperature Range - Operating	-40° to +85°C
Termination Interface Style	Surface Mount

### Solder Process Data

Max-Duration	10
Lead-Free Process Capability	REFLOW
Max-Cycle	2
Max-Temp	245